China

MINKO

CE, ROHS

## LCD Display 300W/500W/700W/1000W Portable Power Station With Solar Panel Waterproof Refurbish

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 5
- Price:

M

MINKO

- Packaging Details:
- Delivery Time:
- Payment Terms: T/T, Wester
- Supply Ability:
- Portable Power Station-M1000 5 pieces negotiation L210xW85xH52 (mm) 8 -10 working days T/T, Western Union, MoneyGram,Paypal,Skrill,Transferwise



ABMINICO

## **Product Specification**

- Rated Power AC:
- Capacity:
- Power Indicate:
- Solar Charging Input:
- Wireless Charge Output:
- Discharging Temperature
- Range:Housing Material:
- Operation Humidity:
- Highlight:
- 999Wh LCD Display 18-23V/3A(60W Max) 10W 14~104°F(-10~40°C )

1000000 pieces per month

ABS+PC

1000W

- 10%~90%
  - 300w portable battery generator for camping , 700w portable battery generator for camping , 24v lithium ion power station



### More Images



#### LCD Display 300W/500W/700W/1000W Portable Power Station With Solar Panel Waterproof Refurbish

#### Features of Portable Power Station

UL certified vehicle level lithium battery

super inverter technology maximum support 1500W equipment (US standard Japanese standard 120V) and maximum support 2000W equipment (Central Europe Australian-British South African standard 230V)

1000W rated output

full large capacity 1 KWH electricity

modeling IP armor warrior

compared to this product size Mini weight light

Apply to: Home emergency, small household appliances, digital products (such as UAV, mobile phone, computer, notebook, camera, handheld head, car refrigerator, etc.), long-distance self-driving travel, outdoor camping, lighting, picnic, wild

fishing,environmental monitoring, geological exploration, car electricity, medical equipment and other scenes.

#### **Product Specification**

| Product Specification            |  |
|----------------------------------|--|
| Rated Power AC                   | 1000W  |
| Capacity                         | 999Wh (22.2V/45A or 3.7V/270000mAh)  |
| Battery type                     | UL Li-ion  |
| Power Indicate                   | LCD display  |
| LCD Display                      | Battery remaining capacity, Battery fault, total output power,Over temperature,input power |
| DC Input                         | DC24V/6.25A(150W max,adapter with UL,CCC,CE,PSE,FCC)                                       |
| DC fully Charging                |  |
| Time                             | About 7~8H   |
| Solar Controller Model           | МРРТ   |
| Solar Charging Input             | 18-23V/3A(60W max)   |
| Charging Temperature<br>Range    | 32~104°F(0°C~40°C)   |
| USB Output                       | Type-C output:PD 60W(5V3A,9V3A,12V3A,15V3A,20V3A)*1  |
|                                  | USB-A output:QC3.0(18W/5V3A,9V2A,12V1.5A)*3(total 54W)                                     |
| Wireless Charge<br>Output        | 10W  |
| Cigarret Lighter output          | 12V/10A(120W)  |
| DC output                        | 12V/5A/DC5521*2(total 120W)  |
| LED light                        | 5W*2(total 10W Max)  |
|                                  | SOS,flashlight   |
| AC Output                        | Output waveform:pure sinewave  |
|                                  | Output voltage:110V(US/JP) or 220V(EU/UK/AU/CN) (AC output                                 |
|                                  | voltage and frequency are customized, according to different                               |
|                                  | countries and regions.Please refer to the actual product)                                  |
|                                  | Output frequency: 50/60Hz  |
|                                  | Peak AC output:2000W   |
|                                  | AC continuous output: 1000W  |
| Discharging<br>Temperature Range | 14~104°F(-10~40°C)   |
| Product size/Weight              | 328*221*263mm/about 8.9Kg  |
| Carton Size/Weight               | 32.5*25*36.5CM/about 11.3Kg/1PCS   |
| Protections                      | over-charging, short-circuit ,low-voltage,over-temperatature and                           |
|                                  | over-discharging protection  |
| Color                            | Oranger+gray,Blue+gray,Red+gray,Green+gray   |
| Housing Material                 | ABS+PC (fireproofing V0)   |
| Working Temperature              | -15~45℃  |
| Operation Humidity               | 10%~90%  |
| Standard Package<br>Include      | 1*M1000 portable power supply, 1*150W power supply, 1*User                                 |
|                                  | Manual, ,color box packaging,1*MC4 charging cable, 1*vehicle                               |
|                                  | charging cable,1*straps  |
| Warrantly                        | 12 months  |
|                                  |  |

#### 9 Protections Strictly Abide By Charging Safety

Overcurrect protection Short-circuit protection Over discharge protection Low temperature protection

High temperature protection

Overvoltage protection

Overload protection

Signal interference protection Overcharge protection





# More use scenarios



 +8613539872669
 Yumiko@szminko.com
 evstationcharger.com

309 West Lake Industrial Zone, Cuishan Road, Dongxiao Street, Luohu District, SZ